


INDUSTRIAL COMPONENT DATA

MCDN 1,5/ 9-G1-3,5 P26THR R56 1826499 PHOENIX CONTACT PCB headers, nominal current: 8 A, rated voltage (III/..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDN 1,5/ 9-G1-3,5 P26THR R56



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDN 1,5/ 9-G1-3,5 P26THR R56
Catalog number	1826499
Category	Printed circuit board connector
Minimum order	110 Pcs
Document ID	EO-7B087379EE
Generated	2026-08-03

Product Overview

PCB headers, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 9, pitch: 3.5 mm, color: black, contact surface: Tin, mounting: THR soldering

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 18, number of rows: 2, number of poles: 9, number of connections: 18, family of articles: MCDN 1.5/.. -G1-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 56 mm wide strap

PCB headers, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 9, pitch: 3.5 mm, color: black, contact surface: Tin, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.6 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1826499

Packing unit 1

GTIN 4046356857673

Custom tariff number 85366930

Drawings

General

[Environmental Product Compliance](#)

[Dimensions](#)

[Standards and Regulations](#)

[Classifications](#)

[Drawings](#)

[Diagram](#)

Type: FMC 1,5/...-ST-3,5 with MCDN 1,5/...-G1-3,5 P26THR

[Back to top](#)[Dimensions](#)

Length [l] 13.3 mm

Width 33 mm

Pitch 3.5 mm

Dimension a 28 mm

Width [w] 33 mm

Height [h] 17.8 mm

Height 15.2 mm

Length of the solder pin 2.6 mm

Pin dimensions 0.8 x 0.8 mm

Length 13.3 mm

[Back to top](#)[General](#)

Range of articles MCDN 1,5/..-G1-THR

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Color black

Number of positions 9

[Back to top](#)[Standards and Regulations](#)

Connection in acc. with standard EN-VDE

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 4.0 27260700

eCl@ss 4.1 27260700

eCl@ss 5.0 27260700

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

[Back to top](#)[ETIM](#)

ETIM 3.0 EC001121

ETIM 4.0 EC002637

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

[Back to top](#)[UNSPSC](#)

UNSPSC 6.01 30211810
UNSPSC 7.0901 39121409
UNSPSC 11 39121409
UNSPSC 12.01 39121409
UNSPSC 13.2 39121409
UNSPSC 18.0 39121409
UNSPSC 19.0 39121409
UNSPSC 20.0 39121409
UNSPSC 21.0 39121409

Back to top

ETIM for 1826499 Connectors (EC002637)

Feature Name

Feature Value

Conn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDN 1,5/ 9-G1-3,5 P26THR R56 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.