

INDUSTRIAL COMPONENT DATA

MCDN 1,5/ 9-G1-3,5 RNP26THR2CP 1799390 PHOENIX CONTACT Housing base for printed circuit board, nominal curre..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDN 1,5/ 9-G1-3,5 RNP26THR2CP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDN 1,5/ 9-G1-3,5 RNP26THR2CP
Catalog number	1799390
Category	Printed circuit board connector
Minimum order	30 Pcs
Document ID	EO-0CA7B5673C
Generated	2026-08-04

Product Overview

Housing base for printed circuit board, nominal current: 8 A, number of poles: 9, pitch: 3.5 mm, color: black, surface of contact: Tin, assembly: Soldering THR

Base housing printed circuit board, nominal section: 1.5 mm², color: black, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Male, Number of potentials: 18, Number of rows: 2, Number of poles per row: 9, number of connections: 18, article family: MCDN 1.5/..-G1-THR, pitch: 3.5 mm, mounting: WELDING THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, Stecksystem: MINI COMBICON, Locking: sin, packing type: boxed packaging PCB headers, nominal cross section: 1.5 mm², color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Pin, number of potentials: 18, number of rows: 2, number of positions: 9, number of connections: 18, product range: MCDN 1,5/..-G1-RN-THR, pitch: 3.5 mm, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Connectors S

Product type PCB headers

Product family MCDN 1,5/..-G1-RN-THR

Number of positions 9
Pitch 3.5 mm
Number of connections 18
Number of rows 2
Mounting flange without
Number of potentials 18
Pin layout Linear pinning
Solder pins per potential 1
Electrical propertiesNominal current I_N 8 A
Nominal voltage U_N 160 V
Degree of pollution 3
Contact resistance 2.1 m Ω
Rated voltage (III/3) 160 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 250 V
Rated surge voltage (II/2) 2.5 kV
MountingMounting type THR soldering
Pin layout Linear pinning
Processing notes
Process Reflow/wave soldering
Moisture Sensitive Level MSL 1
Classification temperature T_c 260 °C
Solder cycles in the reflow 3
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface contact area (top layer) Tin (3 - 5 μm Sn)
Metal surface contact area (middle layer) Nickel (1.3 - 3 μm Ni)
Metal surface soldering area (top layer) Tin (3 - 5 μm Sn)
Metal surface soldering area (middle layer) Nickel (1.3 - 3 μm Ni)
Material data - housing
Color (Housing) black (9005)
Insulating material LCP
Insulating material group IIIa
CTI according to IEC 60112 175
Flammability rating according to UL 94 V0
NotesDetails for soldering processes Processing using ref...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDN 1,5/ 9-G1-3,5 RNP26THR2CP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.