

INDUSTRIAL COMPONENT DATA

MCDV 1,5/10-G1-3,81 OG 1456320 PHOENIX CONTACT Printed circuit board base housing, nominal section: 1.5 mm2,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDV 1,5/10-G1-3,81 OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDV 1,5/10-G1-3,81 OG
Catalog number	1456320
Category	Printed circuit board connector
Minimum order	1000 Pcs
Document ID	EO-3C87FCD003
Generated	2026-08-02

Product Overview

Printed circuit board base housing, nominal section: 1.5 mm2, color: orange, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 2, number of poles: 10, article family: MCDV 1.5/.. -G1, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: without, clamping type: without, packaging type: boxed

Printed circuit board base housing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1456320 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

2

Modular spacing contacts (EF007326)

3.81 mm
Modular spacing connections (EF006827)
3.81 mm
Rated current In (EF008250)
8 A
Rated voltage (EF000228)
160 V
Rated surge voltage (EF002993)
2.5 kV
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Material of contact surface (EF004020)
Tin
Type of electric connection (EF003961)
Other
Diameter connection pin (EF006823)
1.2 mm
Length pin (EF006825)
3.4 mm
Material insulation body (EF007543)
Other
Housing colour (EF000136)
Orange
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-40 °C
Type of fastening (EF002442)
Other
Type of banding (EF007011)
Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDV 1,5/10-G1-3,81 OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.