

INDUSTRIAL COMPONENT DATA

MCR-SL-D-FIT 2864024 PHOENIX CONTACT Digital display

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCR-SL-D-FIT



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCR-SL-D-FIT
Catalog number	2864024
Category	Accessories/spare parts for HVAC sensors
Minimum order	1 Pcs
Document ID	EO-FBEE2029A0
Generated	2026-08-03

Product Overview

Digital display

MCR digital display, for measuring and displaying frequencies, pulses and times, 6-digit display

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2864024

Packing unit 1 pc

Catalog page Page 185 (C-5-2017)

GTIN 4017918976477

Weight per Piece (excluding packing) 92.600 g

Custom tariff number 90291000

Country of origin DE (Germany)

Dimensions

Width 48 mm

Height 24 mm

Depth 68 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 65 °C

Ambient temperature (storage/transport) -25 °C ... 70 °C

Degree of protection IP65 from the front

Input data

Input resistance of voltage input 10 k Ω

Switching output

Output name 1 NPN optocoupler

Maximum switching voltage 30 V DC

Max. switching current 10 mA

Power supply

Supply voltage range 10 V DC ... 30 V DC

Max. current consumption max. 40 mA

General

Noise emission EN 55011 / class B

Noise immunity EN 61000-6-2

Color gray

Housing material Macrolon 2405

Conformance CE-compliant

UL, USA/Canada UL 863

Standards and Regulations

Noise emission EN 55011 / class B

Noise immunity EN 61000-6-2

EN 61000-4-2

Connection in acc. with standard CUL

Conformance CE-compliant

UL, USA/Canada UL 863

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027210301eCl@ss 4.127210301eCl@ss 5.027210301eCl@ss 5.127210300eCl@ss 6.027210300eCl@ss
7.027210301eCl@ss 8.027210301eCl@ss 9.027210301

ETIM 2.0EC001426ETIM 3.0EC001426ETIM 4.0EC001426ETIM 5.0EC001426ETIM 6.0EC001426

UNSPSC 6.0130211506UNSPSC 7.090139121008UNSPSC 1139121008UNSPSC 12.0139121008UNSPSC 13....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCR-SL-D-FIT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.