

INDUSTRIAL COMPONENT DATA

MINI MCR-SL-PTB 2864134 PHOENIX CONTACT Power terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-SL-PTB



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI MCR-SL-PTB
Catalog number	2864134
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-600CCC8F4E
Generated	2026-08-01

Product Overview

Power terminal block

MCR power terminal for several modes. MINI Analog via conect. P. Lanes, with connection. per screw, current absorption up to 2 A max.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2864134

Packing unit 1 pc

Catalog page Page 118 (C-7-2015)

GTIN 4017918974770

Weight per Piece (excluding packing) 69.500 g

Custom tariff number 85437090

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 93.1 mm

Depth 102.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 65 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Output data

Output voltage range Input voltage - 0.8 V

General

Mounting position any

Assembly instructions The T connector can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail according to EN 60715.

Connection data, input

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 12

Stripping length 12 mm

Screw thread M3

Standards and Regulations

Electromagnetic compatibility Conformance with EMC directive

Noise emission EN 61000-6-4

Connection in acc. with standard CUL

Standards/regulations EN 61000-4-2

Designation Electromagnetic RF field

Standards/regulations EN 61000-4-3

Evaluation criterion A

Standards/regulations EN 61000-4-4

EN 61000-4-5

Designation Conducted interferences

Standards/regulations EN 61000-4-6

Evaluation criterion A

Conf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-SL-PTB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.