

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 2-G-3,5-RNGYP26AUTHRR 1779682 PHOENIX CONTACT Housing base printed circuit board, nominal current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 2-G-3,5-RNGYP26AUTHRR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 2-G-3,5-RNGYP26AUTHRR
Catalog number	1779682
Category	Printed circuit board connector
Minimum order	200 Pcs
Document ID	EO-B4EC9E2214
Generated	2026-08-04

Product Overview

Housing base printed circuit board, nominal current: 8 A, voltage and sizing (III/2): 160 V, number of poles: 2, pitch: 3.5 mm, color: gray, surface, contacts: Gold, assembly: Soldering THR, you will Find more information for the user, and design recommendations on technology, Through Hole Reflow in 'Downloads'

Printed circuit board base housing, nominal section: 1.5 mm², color: gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MCV 1.5/.. -G-RN-THR, pitch: 3.5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: box-packed, More user information and design recommendations on Through Hole Reflow technology can be found at: Downloads

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

PCB base strip, Rated current: 8 A, Rated voltage (III/2): 160 V, Number of poles: 2, Pitch: 3.5 mm, Colour: grey, Contact surface: Gold, Mounting: THR soldering, User information and design recommendations for Through Hole Reflow technology can be found under 'Downloads'

Commercial data

Order key 1779682

Packaging unit 200 PCS
Sales key E1 - PCB Connector
Minimum Order Quantity 200 PCS
Note Made-to-order production (no returns)
GTIN 4046356531269
Weight per piece (excluding packaging) 2,215 g
Weight per piece (including packaging) 2,714 g
Customs tariff number 85366930
Country of origin DE (Germany)
Environmental Product Compliance
China RoHS Period of intended use: unlimited = EFUP-e
No hazardous substances above the limit values
Classifications
eCl@ss
eCl@ss 4.0 Reference 272607xx
eCl@ss 4.1 27260701
eCl@ss 5.0 27260701
eCl@ss 5.1 27260700
eCl@ss 6.0 27260700
eCl@ss 7.0 27440402
eCl@ss 8.0 27440402
eCl@ss 9.0 27440402
ETIM
ETIM 4.0 EC002637
ETIM 5.0 EC002637
ETIM 6.0 EC002637
ETIM 7.0 EC002637
UNSPSC
UNSPSC 6.01 30211810
UNSPSC 7.0901 39121409
UNSPSC 11 39121409
UNSPSC 12.01 39121409
UNSPSC 13.2 39121409
ETIM for 1779682 Connectors (EC002637)
Feature Name
Feature Value
Connector model (EF007495)
Fixed connector
Contact type (EF001587)
Pin
Number of poles (EF001391)
2
Number of plug-in contact rows (EF006935)
1
Modular spacing contacts (EF007326)
3.5 mm
Modular spacing connections (EF006827)

3.5 mm

Rated current In (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 2-G-3,5-RNGYP26AUTHRR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.