


INDUSTRIAL COMPONENT DATA

MCV 1,5/20-G-3,5-RN GY 1710693 PHOENIX CONTACT

Housing base printed circuit board, number of poles: 20, pitch..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/20-G-3,5-RN GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/20-G-3,5-RN GY
Catalog number	1710693
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-F9B85835D7
Generated	2026-08-06

Product Overview

Housing base printed circuit board, number of poles: 20, pitch: 3.5 mm, color: gray, surface contacts: Tin
Printed circuit board base housing, nominal section: 1.5 mm², color: gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 20, number of rows: 1, number of poles: 20, number of connections: 20, family of articles: MCV 1.5/.. -G-RN, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Socket for printed circuits, nominal current: 8 A, rated operating voltage (III/2): 160 V, number of poles: 20, pitch: 3.5 mm, color: gray, surface of contact: Tin, assembly: Soldering wave

Commercial data

The code for the order One million seven hundred ten thousand six hundred ninety three

Pieces/pack. 50 PCS

Sales key AAAEDA -

The amount of minimum order 50 PCS

GTIN Four trillion fifty five billion six hundred twenty six million one hundred sixty nine thousand nine hundred ten

Weight per piece (package included) 5,280 g

Number customs tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Environmental Product Compliance

China RoHS Period for proper use: unlimited = EFUP-and

Any hazardous substances above the threshold values

Rankings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 6.0 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 8.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 9.0 Twenty seven million four hundred forty thousand four hundred two

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

UNSPSC

UNSPSC 13.2 Thirty nine million one hundred twenty one thousand four hundred nine

ETIM for 1710693 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

20

Number of plug-in contact r...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/20-G-3,5-RN GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.