

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 3-G-3,5-RN GY35 1170483 PHOENIX CONTACT

Printed circuit board base housing, nominal section: 1.5 mm..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 3-G-3,5-RN GY35



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 3-G-3,5-RN GY35
Catalog number	1170483
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-89632090CD
Generated	2026-08-05

Product Overview

Printed circuit board base housing, nominal section: 1.5 mm², color: light gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 3, family of articles: MCV 1.5/.. -G-RN, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON FMC 1.5 - MCDN 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, clamping type: Socket protrusion, packaging type: boxed

Base housing printed circuit board, nominal section: 1.5 mm², color: light gray, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Male, Number of rows: 1, Number of poles per row: 3, article family: MCV 1,5/.. -G-RN, pitch: 3.5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, Stecksystem: MINI COMBICON, Locking: Lace locking, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

ETIM for 1170483 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rated current I_n (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

3.4 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Grey

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of fastening (EF002442)

Other

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 3-G-3,5-RN GY35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.