

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 3-G-3,5-RNGYP26AUTHRR 1779598 PHOENIX CONTACT Housing base printed circuit board, nominal current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 3-G-3,5-RNGYP26AUTHRR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 3-G-3,5-RNGYP26AUTHRR
Catalog number	1779598
Category	Printed circuit board connector
Minimum order	200 Pcs
Document ID	EO-B4A02470E7
Generated	2026-08-06

Product Overview

Housing base printed circuit board, nominal current: 8 A, voltage and sizing (III/2): 160 V, number of poles: 3, pitch: 3.5 mm, color: gray, surface, contacts: Gold, assembly: Soldering THR, you will Find more information for the user, and design recommendations on technology, Through Hole Reflow in 'Downloads'

Printed circuit board base case, nominal section: 1.5 mm², color: gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MCV 1.5/.. -G-RN-THR, pitch: 3.5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: box-packed, More user information and design recommendations on Through Hole Reflow technology can be found at: Downloads

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Housing base printed circuit board, nominal current: 8 A, voltage and sizing (III/2): 160 V, number of poles: 3, pitch: 3.5 mm, color: gray, surface, contacts: Gold, assembly: Soldering THR, you will Find more information for the user, and design recommendations on technology, Through Hole Reflow in 'Downloads'

Data commercial

Key order One million seven hundred seventy nine thousand five hundred ninety eight

Packing unit 200 pcs

Key selling AAAEDB -

Minimum order quantity 200 pcs

EAN Four trillion forty six billion three hundred fifty six million five hundred thirty one thousand three hundred seventy five

Unit weight (excluding packaging) 2,950 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin DE (Germany)

Environmental Product Compliance

China RoHS Space of time for the intended use: unlimited = FEUP-e

No dangerous substances above the thresholds

Ratings

eCl@ss

eCl@ss 4.0 272607xx

eCl@ss 4.1 Twenty seven million two hundred sixty thousand seven hundred one

eCl@ss 5.0 Twenty seven million two hundred sixty thousand seven hundred one

eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 6.0 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 8.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 9.0 Twenty seven million four hundred forty thousand four hundred two

ETIM

ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 3-G-3,5-RNGYP26AUTHRR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.