

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 3-G-3,81 VPE500 1736133 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 3-G-3,81 VPE500



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 3-G-3,81 VPE500
Catalog number	1736133
Category	Printed circuit board connector
Minimum order	500 Pcs
Document ID	EO-F1F9684939
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base case, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MCV 1.5/..-G, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

PCB headers, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Pin, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MCV 1,5/..-G, pitch: 3.81 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family MCV 1,5/..-G

Product line COMBICON Connectors S

Number of positions 3

Pitch 3.81 mm

Number of connections 3
Number of rows 1
Number of potentials 3
Mounting flange without
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 02
Electrical propertiesNominal current I_N 8 A
Nominal voltage U_N 160 V
Contact resistance 1.2 m Ω
Rated voltage (III/3) 160 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 250 V
Rated surge voltage (II/2) 2.5 kV
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface contact area (top layer) Tin (3 - 5 μm Sn)
Metal surface contact area (middle layer) Nickel (1 - 3 μm Ni)
Metal surface soldering area (top layer) Tin (3 - 5 μm Sn)
Metal surface soldering area (middle layer) Nickel (1 - 3 μm Ni)
Material data - housing
Color (Housing) green (6021)
Insulating material PBT
Insulating material group IIIa
CTI according to IEC 60112 225
Flammability rating according to UL 94 V0
DimensionsDimensional drawing
Pitch 3.81 mm
Width [w] 12.82 mm
Height [h] 12.6 mm
Length [l] 7.25 mm
Installed height 9.2 mm
Solder pin length [P] 3.4 mm
Pin dimensions 0.8 x 0.8 mm
PCB design
H...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 3-G-3,81 VPE500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.