

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 3-GF-5,08 BK 1050072 PHOENIX CONTACT

Feed-through header MCV 1,5/ 3-GF-5,08 BK 1050072

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 3-GF-5,08 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 3-GF-5,08 BK
Catalog number	1050072
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-A9F1F374FC
Generated	2026-08-03

Product Overview

Feed-through header - MCV 1,5/ 3-GF-5,08 BK - 1050072

Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MCV 1.5/.. -GF, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB headers, nominal current: 8 A, rated voltage (III/2): 320 V, number of positions: 3, pitch: 5.08 mm, color: black, contact surface: Tin, mounting: Wave soldering

Key Commercial Data

Orderkey 1050072

Packing unit 1

GTIN 4055626663418

Custom tariff number 85366930

Dimensions

Length [L] 7.25 mm

Width 24.36 mm

Pitch 5.08 mm

Dimension a 10.16 mm

Width [w] 24.36 mm

Height [h] 12.6 mm

Height 9.2 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 7.25 mm

General

Range of articles MCV 1,5/..-GF

Color black

Number of positions 3

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 3-GF-5,08 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.