

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 4-G-3,5 THT PIN2,6R32 1728413 PHOENIX CONTACT PCB base housing, color: black, surface contacts: tin..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 4-G-3,5 THT PIN2,6R32



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 4-G-3,5 THT PIN2,6R32
Catalog number	1728413
Category	Printed circuit board connector
Minimum order	200 Pcs
Document ID	EO-6608056F95
Generated	2026-08-04

Product Overview

PCB base housing, color: black, surface contacts: tin, number of poles: 4, item family: MCV 1.5/.. -G-THT, pitch: 3.5 mm, pin arrangement: Linear pin layout, More user information and design recommendations on Through Hole Reflow technology can be found at: [Downloads](#)

PCB headers, color: black, contact surface: Tin, number of positions: 4, product range: MCV 1,5/..-G-THT, pitch: 3.5 mm, pin layout: Linear pinning, For user information and design recommendations for through-hole reflow technology, go to: [Downloads](#)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesType Component suitable for through hole reflow

Product type PCB headers

Product family MCV 1,5/..-G-THT

Number of positions 4

Pitch 3.5 mm

Mounting flange no

Pin layout Linear pinning

Electrical propertiesMaximum load current 8 A (per position)

Rated voltage (II/2) 320 V

Rated voltage (III/2) 160 V

Rated surge voltage (II/2) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (III/3) 2.5 kV
MountingMounting type THR soldering
Pin layout Linear pinning
Material specificationsColor black
Flammability rating according to UL 94 V0
Insulating material group IIIa
Insulating material PA-GF
Contact surface Tin Sn
DimensionsInstalled height 10 mm
Hole diameter 1.4 mm
Pitch 3.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 4-G-3,5 THT PIN2,6R32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.