

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 4-G-3,81 VPE500 1919019 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 4-G-3,81 VPE500



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 4-G-3,81 VPE500
Catalog number	1919019
Category	Printed circuit board connector
Minimum order	500 Pcs
Document ID	EO-E8DD2C5076
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MCV 1.5/.. -G, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1919019

Packing unit 1

GTIN 4017918482527

Custom tariff number 85366930

Dimensions

Length [L] 7.25 mm

Width 16.63 mm

Pitch 3.81 mm

Dimension a 11.43 mm

Width [w] 16.63 mm

Height [h] 12.6 mm

Height 9.2 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 7.25 mm

General

Range of articles MCV 1,5/..-G

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Color green

Number of positions 4

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1919019 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

4

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.81 mm

Modular spacing connections (EF006827)

3.81 mm

Rated current In (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of cont...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 4-G-3,81 VPE500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.