

## INDUSTRIAL COMPONENT DATA

# MCV 1,5/ 5-G-3,5 BK CP2 1046645 PHOENIX CONTACT

## Housing base printed circuit board, number of poles: 5, pitc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 5-G-3,5 BK CP2



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | MCV 1,5/ 5-G-3,5 BK CP2         |
| Catalog number  | 1046645                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1000 Pcs                        |
| Document ID     | EO-65544F2DF2                   |
| Generated       | 2026-08-06                      |

### Product Overview

Housing base printed circuit board, number of poles: 5, pitch: 3.5 mm, color: black

Printed circuit board base case, nominal section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 5, family of articles: MCV 1.5/.. -G, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

PCB headers, nominal cross section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Pin, number of rows: 1, number of positions: 5, product range: MCV 1,5/..-G, pitch: 3.5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family MCV 1,5/..-G

Product line COMBICON Connectors S

Number of positions 5

Pitch 3.5 mm

Number of rows 1  
Pin layout Linear pinning  
Solder pins per potential 1  
Data management status  
Article revision 00  
Electrical propertiesNominal current IN 8 A  
Nominal voltage UN 160 V  
Contact resistance 1.8 m?  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 160 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 250 V  
Rated surge voltage (II/2) 2.5 kV  
MountingMounting type Wave soldering  
Pin layout Linear pinning  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface contact area (top layer) Tin (3 - 5 µm Sn)  
Metal surface contact area (middle layer) Nickel (1 - 3 µm Ni)  
Metal surface soldering area (top layer) Tin (3 - 5 µm Sn)  
Metal surface soldering area (middle layer) Nickel (1 - 3 µm Ni)  
Material data - housing  
Color (Housing) black (9005)  
Insulating material PBT  
Insulating material group IIIa  
CTI according to IEC 60112 225  
Flammability rating according to UL 94 V0  
DimensionsDimensional drawing  
Pitch 3.5 mm  
Width [w] 18.9 mm  
Height [h] 12.6 mm  
Length [l] 7.25 mm  
Installed height 9.2 mm  
Solder pin length [P] 3.4 mm  
Pin dimensions 0.8 x 0.8 mm  
PCB design  
Hole diameter 1.2 mm  
Mechanical testsVisual inspection  
Specification IEC 60...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 5-G-3,5 BK CP2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.