

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 6-G-3,5 BD:X12 1712522 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 6-G-3,5 BD:X12



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 6-G-3,5 BD:X12
Catalog number	1712522
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-79D378F9B9
Generated	2026-08-04

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: MCV 1.5/.. -G, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1712522

Packing unit 1

GTIN 4055626289304

Custom tariff number 85366930

Dimensions

Length [L] 7.25 mm

Width 8.4 mm

Pitch 3.5 mm

Dimension a 17.5 mm

Width [w] 8.4 mm

Height [h] 12.6 mm

Height 9.2 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 7.25 mm

General

Range of articles MCV 1,5/..-G

Insulating material group IIIa

Rated voltage (III/2) 160 V

Nominal current IN 8 A

Flammability rating according to UL 94 V0

Color green

Number of positions 6

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 5.0EC002637ETIM 6.0EC002637

ETIM for 1712522 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

6

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rated current In (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

3.4 mm

Material insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 6-G-3,5 BD:X12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.