

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 8-G-3,5-RN GYP26AUTHR 1779624 PHOENIX CONTACT Housing base printed circuit board, nominal current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 8-G-3,5-RN GYP26AUTHR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 8-G-3,5-RN GYP26AUTHR
Catalog number	1779624
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-77B671CB64
Generated	2026-08-05

Product Overview

Housing base printed circuit board, nominal current: 8 A, voltage and sizing (III/2): 160 V, number of poles: 8, pitch: 3.5 mm, color: gray, surface, contacts: Gold, assembly: Soldering THR

Printed circuit board base housing, nominal section: 1.5 mm², color: gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: MCV 1.5/.. -G-RN-THR, pitch: 3.5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Snap-on protrusion, packing type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

PCB base strip, rated current: 8 A, rated voltage (III/2): 160 V, number of poles: 8, pitch: 3.5 mm, color: gray, contact surface: gold, mounting: THR soldering

Commercial data

Order key 1779624

Packaging unit 50 PCS

Sales key E1 - PCB Connector

Note Made-to-order production (no returns)

GTIN 4046356531238

Weight per piece (excluding packaging) 1,966 g

Weight per piece (including packaging) 1,966 g

Customs tariff number 85366930

Country of origin DE (Germany)

Environmental Product Compliance

China RoHS Period of intended use: unlimited = EFUP-e

No hazardous substances above the limit values

Classifications

eCl@ss

eCl@ss 4.0 Reference 272607xx

eCl@ss 4.1 27260701

eCl@ss 5.0 27260701

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

ETIM

ETIM 4.0 EC002637

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

UNSPSC

UNSPSC 6.01 30211810

UNSPSC 7.0901 39121409

UNSPSC 11 39121409

UNSPSC 12.01 39121409

UNSPSC 13.2 39121409

ETIM for 1779624 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

8

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rated current I_n (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Gold

Type of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 8-G-3,5-RN GYP26AUTHR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.