


INDUSTRIAL COMPONENT DATA

ZFKKDS 1,5C-5,0 PA1 1703564 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKKDS 1,5C-5,0 PA1



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKKDS 1,5C-5,0 PA1
Catalog number	1703564
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-0DA82ABC4D
Generated	2026-08-06

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 16 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 0, number of rows: 2, number of poles per row: 1, article family: ZFKKDS(A) 1.5C, pitch: 5 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.7 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1703564

Packing unit 1

GTIN 4046356657556

Custom tariff number 85472000

Dimensions

Length [l] 21 mm

Pitch 5 mm

Width [w] 5 mm

Height 26 mm

Height [h] 29.7 mm

Solder pin [P] 3.7 mm

Hole diameter 1.1 mm

General

Range of articles ZFKKDS(A) 1,5C

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 16 A

Nominal cross section 1.5 mm²

Solder pin surface

Internal cylindrical gage A1

Stripping length 7 mm

Number of positions 1

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 14

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0271411111eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss

7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC

13.239121432

ETIM for 1703564 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

29.7 mm

Number of electrical connections (EF008252)

0

Number of levels (EF002659)

2

Modular spacing connections (EF006827)

5 mm

Rated current In (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKKDS 1,5C-5,0 PA1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.