

**INDUSTRIAL COMPONENT DATA**

# VIP-3/SC/2FLK14/AN/2P/S7-1500A 2908464 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/SC/2FLK14/AN/2P/S7-1500A



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | VIP-3/SC/2FLK14/AN/2P/S7-1500A |
| Catalog number  | 2908464                        |
| Category        | Interface module               |
| Minimum order   | 1 Pcs                          |
| Document ID     | EO-5BC83101C6                  |
| Generated       | 2026-08-04                     |

## Product Overview

Passive module

VARIOFACE COMPACT LINE interconnect module for Siemens S7-1500 systems with specific marking S7-1500, for channels 1 - 16, with screw connection, module width: 82.5 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                             |
|--------------|---------------------------------------------|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |
|--------------|---------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2908464

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 513 (C-5-2017)

GTIN 4055626357676

Weight per Piece (excluding packing) 214.100 g

Custom tariff number 85366990

Country of origin US (United States)

Dimensions

Width 82.5 mm

Height 68.8 mm

Depth 60.7 mm

**Ambient conditions**

Ambient temperature (operation) -20 °C ... 60 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

**General**

Max. perm. operating voltage 60 V AC/DC

Max. perm. current (per branch) 1 A

Max. permissible current (separate power supply) 7 A

Number of positions 14

Status display No

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Screw connection

Stripping length 8 mm

Screw thread M 3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 2

Number of positions 14

Pitch 2.54 mm

Supported controller

Controller SIEMENS S7-1500

- suitable I/O card 6ES7 531-7KF00-0AB0

6ES7 531-7NF00-0AB0

6ES7 531-7NF10-0AB0

6ES7 531-7PF00-0AB0

6ES7 532-5HF00-0AB0

6ES7 532-5HD00-0AB0

6ES7 532-5ND00-0AB0

Standards and Regulations

Standards/regulations IEC 60664

DIN EN 50178

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads",....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/SC/2FLK14/AN/2P/S7-1500A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.