

INDUSTRIAL COMPONENT DATA

MCVR 1,5/ 6-ST-3,5 BK BDWH:-/C 1828031 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCVR 1,5/ 6-ST-3,5 BK BDWH:-/C



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCVR 1,5/ 6-ST-3,5 BK BDWH:-/C
Catalog number	1828031
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-1270AED3DA
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, article family: MCVR 1.5/. -ST, pitch: 3.5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, driver/printed circuit board connection direction: 90 °, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1828031

Packing unit 1

GTIN 4046356864688

Custom tariff number 85366990

Dimensions

Length [l] 10.4 mm

Width [w] 21.8 mm

Height [h] 19.1 mm

Pitch 3.5 mm

Dimension a 17.5 mm

General

Range of articles MCVR 1,5/...-ST

Number of positions 6

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.08 mm²

2 conductors with same cross section, solid max. 0.5 mm²

2 conductors with same cross section, stranded min. 0.08 mm²

2 conductors with same cross section, stranded max. 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.34 mm²

2 conductors with same cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCVR 1,5/ 6-ST-3,5 BK BDWH:-/C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.