

INDUSTRIAL COMPONENT DATA

PLC-RPT- 12DC/21/MS 2909666 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-12DC/21/MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-12DC/21/MS
Catalog number	2909666
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-413629420C
Generated	2026-08-02

Product Overview

Relay Module

PLC-INTERFACE, consisting of PLC-BPT.../21 base terminal block with push-in connection and plug-in miniature relay with power contact and manual operation, 1 switched contact, input voltage 12 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataNotes on operation Separating plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or FBST 500....

Product propertiesProduct type Relay Module

Product family PLC-INTERFACE

Application Palm switch

Operating mode 100% operating factor

Mechanical service life 1x 10⁷cycles

Data management status

Date of last data management 01.07.2024

Article revision 03

Electrical propertiesMaximum power dissipation for nominal condition 0.18 W

Test voltage (Winding/contact) 4 kV AC (50 Hz, 1 min., winding/contact)

Insulation characteristics: Coil/contact
Rated insulation voltage 250 V
Rated impulse withstand voltage 6 kV
Overvoltage category III
Degree of pollution 3
Input dataCoil side
Nominal input voltage UN 12 V DC
Input voltage range 9.7 V DC ... 16.8 V DC (20 °C)
Nominal voltage (plugged-in electromechanical relay) 12 V DC
Drive and function monostable
Drive (polarity) polarized
Typical input current at UN 15.3 mA
Typical response time 5 ms
Typical release time 8 ms
Protective circuit Reverse polarity protection; Polarity protection diode
Surge protection; Freewheeling diode
Operating voltage display Yellow LED
Output dataSwitching
Contact switching type 1 changeover contact
Type of switch contact Single contact
Contact material AgSnO
Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-12DC/21/MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.