

INDUSTRIAL COMPONENT DATA

MKDS 1/ 2-3,5 HT BK PIN1,65 1715099 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1/ 2-3,5 HT BK PIN1,65



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 1/ 2-3,5 HT BK PIN1,65
Catalog number	1715099
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-1949BDE48E
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, dimensioning voltage (III/2): 200 V, nominal section: 1.5 mm², Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, family of articles: MKDS 1/.. -HT, pitch: 3.5 mm, connection type: Screw connection with traction capsule, mounting: Weld THR, connection direction driver/printed circuit board: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 1.65 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1715099

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356103565

Weight per Piece (excluding packing) 1.480 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [L] 7.3 mm

Pitch 3.5 mm

Dimension a 3.5 mm

Width [w] 7.5 mm

Height 8.5 mm

Height [h] 10.15 mm

Solder pin [P] 1.65 mm

Pin spacing 3.5 mm

Hole diameter 1.1 mm

General

Range of articles MKDS 1/..-HT

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 200 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 10 A

Nominal cross section 1 mm²

Maximum load current 12 A

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 5 mm

Number of positions 2

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1/ 2-3,5 HT BK PIN1,65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.