


INDUSTRIAL COMPONENT DATA

MDSTBVA 2,5/ 3-G-5,08 GY 1701428 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MDSTBVA 2,5/ 3-G-5,08 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MDSTBVA 2,5/ 3-G-5,08 GY
Catalog number	1701428
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-3A46B8398D
Generated	2026-08-04

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm², color: gray, nominal current: 10 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, Number of potentials: 6, Number of rows: 2, Number of poles per row: 3, number of connections: 6, family of articles: MDSTBVA 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, Stecksystem: CLASSIC COMBICON, Locking: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1701428

Packing unit 1

GTIN 4046356534642

Custom tariff number 85366930

Dimensions

Length [l] 23.7 mm

Width 19.78 mm

Pitch 5.08 mm

Dimension a 10.16 mm

Width [w] 19.78 mm

Height [h] 25.9 mm

Height 22 mm

Length of the solder pin 3.9 mm

Pin dimensions 1 x 1 mm

Length 23.7 mm

General

Range of articles MDSTBVA 2,5/..-G

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Color gray

Number of positions 3

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MDSTBVA 2,5/ 3-G-5,08 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.