

INDUSTRIAL COMPONENT DATA

ME 12,5 UTG/FE BUGY 1101908 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catch, tall..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 12,5 UTG/FE BUGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 12,5 UTG/FE BUGY
Catalog number	1101908
Category	Electronic enclosure
Minimum order	500 Pcs
Document ID	EO-9944DF0A8E
Generated	2026-08-05

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, without vents, width: 12.6 mm, height: 99 mm, depth: 107.3 mm, cross connection: without bus connector, number of positions cross connector: not relevant, color: blue grey (7031)

Rail box, Bottom of the box with metal pin, with FE contact, high design, without ventilation slits, width: 12.6 mm, height: 99 mm, depth: 107.3 mm, color: bluish gray (7031), cross bridge: without bus connector, number of poles cross connector: not relevant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 1101908

Packing unit 1

GTIN 4055626960937

Custom tariff number 85389099

Item properties

Material data

PCB data

Packaging information

Classifications

[Dimensions](#)

[Ambient conditions](#)

[General information](#)

[Standards and regulations](#)

[Item properties](#)

[Brief article description](#) Mounting base housing

Type ME 12,5 UTG/FE BUGY

Order No. 1101908

Housing type DIN rail housing

Type Lower housing part with metal foot catch, tall design

Max. IP code to attain IP20

Mounting type DIN rail mounting

Ventilation openings present no

[Back to top](#)[Dimensions](#)

Width [w] 12.6 mm

Height [h] 99 mm

Depth [d] 107.3 mm

Depth from top edge of DIN rail [d] 99.8 mm

Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm

[Back to top](#)[Material data](#)

Color (RAL) blue grey (7031)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)[Ambient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)[PCB data](#)

Number of PCB holders 1

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

[Back to top](#)[General information](#)

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Type of note Recommendation

Note Material of contact pads for bus connector, galvanic gold (hard gold)

[Back to top](#)[Pac...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 12,5 UTG/FE BUGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.