

INDUSTRIAL COMPONENT DATA

ME 17,5-KIT-MSTBO-7035+4PSPT3 1343032 PHOENIX CONTACT DIN rail box, for mounting on DIN rail, closed housing..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 17,5-KIT-MSTBO-7035+4PSPT3



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 17,5-KIT-MSTBO-7035+4PSPT3
Catalog number	1343032
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-1EFBE61368
Generated	2026-08-06

Product Overview

DIN rail box, for mounting on DIN rail, closed housing top, color: light gray (similar RAL 7035), width: 17.6 mm, height: 99 mm, depth: 113.65 mm, incl. 4 pcs of PCB connectors, 3 poles, push-in spring connection, for 2.5 mm², rated current: 12 A, 320 V, Printed circuit board surface: 7800 mm²

Rail housing, for DIN rail mounting, top of closed housing, colour: luminous grey (7035), width: 17.6 mm, height: 99 mm, depth: 113.65 mm, incl. 4 PCB connector units, 3 poles, push-in spring connection, for 2.5 mm², rated current: 12 A, 320 V, printed circuit board surface: 7800 mm²

DIN rail housing, for mounting on a DIN rail, closed upper housing part, color: light grey (7035), width: 17.6 mm, height: 99 mm, depth: 113.65 mm, incl. 4 PCB connectors, 3-pos., Push-in spring connection, for 2.5 mm², nominal current: 12 A, 320 V, PCB surface: 7800 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.

General Material of contact pads for bus connector, galvanic gold (hard gold)

General The PCB surface specification is for orientation purposes and is based on a basic PCB. The housing can also accommodate several PCBs.

Product propertiesProduct type Stackable housing set

Product family ME 17,5
Number of positions 12
Max. number of positions 12 (pitch: 5 mm)
Number of rows 2
Type for mounting on a DIN rail, closed upper housing part
incl. 4 PCB connectors, 3-pos., Push-in spring connection, for 2.5 mm², nominal current: 12 A, 320 V
Housing type DIN rail housing
Ventilation openings present yes
Housing series ME
Connection dataConnection method Push-in spring connection
DimensionsDimensional drawing
Width 17.6 mm
Height 99 mm
Depth 113.65 mm
Depth from top edge of DIN rail 107 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor light grey (7035)
Flammability rating according to UL 94 V0
Surface characteristics untreated
Housing material Polyamide
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) max. 80 %
PCB dataNumber of PCB holders 1
Type of PCB mount Latching
Total PCB surface 7800 mm²
Thickness...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 17,5-KIT-MSTBO-7035+4PSPT3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.