

INDUSTRIAL COMPONENT DATA

ZFKDSA 1-V-3,81- 8 1891043 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKDSA 1-V-3,81-8



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKDSA 1-V-3,81-8
Catalog number	1891043
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-E319BC903C
Generated	2026-08-06

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 12 A, rated voltage (III/2): 200 V, rated cross-section: 1 mm², number of potentials: 8, number of rows: 1, number of poles per row: 8, article family: ZFKDS(A) 1-V, pitch: 3.81 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of welding pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1891043

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918413439

Weight per Piece (excluding packing) 8.830 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [L] 15.9 mm

Pitch 3.81 mm

Height 16 mm

Solder pin [P] 3.5 mm

Hole diameter 1.2 mm

General

Range of articles ZFKDS(A) 1-V

Nominal cross section 1 mm²

Solder pin surface

Number of positions 8

Standards and Regulations

Connection in acc. with standard CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss

7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC

13.239121432

ETIM for 1891043 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

18.75 mm

Number of electrical connections (EF008252)

8

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

3.81 mm

Rated current I_n (EF008250)

12 A

Rated voltage (EF000228)

200 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKDSA 1-V-3,81-8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.