

INDUSTRIAL COMPONENT DATA

ME 22,5 OT-1MSTBO KMGY S1390 1110784 PHOENIX CONTACT DIN rail housing, Upper housing part for connectors wit..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 OT-1MSTBO KMGY S1390



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 OT-1MSTBO KMGY S1390
Catalog number	1110784
Category	Electronic enclosure
Minimum order	50 Pcs
Document ID	EO-2C89F14C57
Generated	2026-08-06

Product Overview

DIN rail housing, Upper housing part for connectors with header, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: light gray (7035)

Rail housing, Top of the connector housing with base housing, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: light gray (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 1110784

Packing unit 1

GTIN 4063151025274

Custom tariff number 85389099

Item properties

Material data

PCB data

Vibration test

Thermostability (Ball Thrust Test)

Degrees of protection provided by housings (IP code)

Packaging information

Classifications

Dimensions

Ambient conditions

Mechanical strength/tumbling barrel

Shock

Test for assessing the risk of fire (glow wire)

General information

Standards and regulations

Item properties

Brief article description Upper part of housing

Type ME 22,5 OT-1MSTBO KMGY S1390

Order No. 1110784

Housing type DIN rail housing

Type Upper housing part for connectors with header

Max. IP code to attain IP20

Mounting type Latching with lower housing part

Number of levels 1

Connection levels 1 (Single-sided)

Max. number of positions 5 (pitch: 3.5 mm)

4 (pitch: 5 mm)

3 (pitch: 7.25 mm)

[Back to top](#)Dimensions

Width [w] 22.6 mm

Height [h] 99 mm

Depth [d] 45.85 mm

Depth from base support surface [d] 38.5 mm

[Back to top](#)Material data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)PCB data

Number of PCB holders 1

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

[Back to top](#)Mechan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 OT-1MSTBO KMGY S1390 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.