


**INDUSTRIAL COMPONENT DATA**

# ME 22,5 OT-MSTBO BU 2908948 PHOENIX CONTACT Upper part of housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 OT-MSTBO BU



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME 22,5 OT-MSTBO BU              |
| Catalog number  | 2908948                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 100 Pcs                          |
| Document ID     | EO-DE62D80717                    |
| Generated       | 2026-08-05                       |

## Product Overview

Upper part of housing

Rail housing, Top of connector housing with base housing, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: blue (5015)

DIN rail housing, Upper housing part for connectors with header, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: blue (similar RAL 5015)

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Housing (HS)

## Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Upper housing part

Housing type DIN rail housing

Housing series ME

Product family ME 22,5..

Number of positions 16

Max. number of positions 20 (pitch: 3.5 mm)

16 (pitch: 5 mm)

12 (pitch: 7.25 mm)

Number of rows 2

Type Upper housing part for connectors with header

Ventilation openings present no  
Data management status  
Article revision 00  
DimensionsDimensional drawing  
Width 22.6 mm  
Height 99 mm  
Depth 45.85 mm  
Depth from base support surface 38.5 mm  
PCB design  
PCB thickness 1.4 mm ... 1.8 mm  
Material specificationsColor (Housing) blue (RAL 5015)  
Flammability rating according to UL 94 V0  
CTI according to IEC 60112 600  
Housing material Polyamide  
Surface characteristics untreated  
Environmental and real-life conditionsVibration test  
Specification IEC 60068-2-6:2007-12  
Frequency 10 - 150 - 10 Hz  
Sweep speed 1 octave/min  
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)  
Acceleration 2g (58.1 Hz ... 150 Hz)  
Test duration per axis 2.5 h  
Test directions X-, Y- and Z-axis  
Glow-wire test  
Specification IEC 60695-2-11:2014-02  
Temperature 850 °C  
Time of exposure 30 s  
Thermal stability / ball thrust test  
Specification IEC 60695-10-2:2014-02  
Temperature 125 °C  
Test duration 1 h  
Force 20 N  
Mechanical strength / tumbling barrel  
Specification IEC 60998-1:2002-12  
Height of fall 50 cm  
Frequency 10  
Shocks  
Specification IEC 60068-2-27:2008-02  
Pulse shape Half-sine  
Acceleration 15g  
Shock dur...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 OT-MSTBO BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.