

INDUSTRIAL COMPONENT DATA

ME 22,5 TBUS 1,5/4P1S BK 2203852 PHOENIX CONTACT DIN rail connector for ME and ME-MAX, design width: 22.5 mm..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 TBUS 1,5/4P1S BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 TBUS 1,5/4P1S BK
Catalog number	2203852
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-18DB423B44
Generated	2026-08-06

Product Overview

ME 22,5 TBUS 1,5/4P1S BK 2203852 PHOENIX CONTACT DIN rail connector for ME and ME-MAX, design width: 22.5 mm..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Modular spacing contacts (EF007326)	3.81 mm
Modular spacing connections (EF006827)	3.81 mm
Rated current In (EF008250)	8 A
Rated voltage (EF000228)	50 V
Rated surge voltage (EF002993)	0.8 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Type of electric connection (EF003961)	Other
Suitable for PCB thickness (EF007253)	1.8 mm
Material insulation body (EF007543)	Other
Housing colour (EF000136)	Black
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C
Type of fastening (EF002442)	Other

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

DIN rail connector for ME and ME-MAX, design width: 22.5 mm, 4 parallel positions and 1 serial position, color: black
Rail bus connectors, color: black, rated current: 8 A, 8 A (parallel contacts) (serial contacts), rated voltage (III/2): 50 V,
number of poles: 5, pitch: 3.81 mm, mounting: Rail mounting, lock: without, fixing type: without, Item with gold contacts, bus
connector for connection with electronics housings

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 TBUS 1,5/4P1S BK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.