


INDUSTRIAL COMPONENT DATA

ME 22,5 TBUS 1,5/ 5-ST-3,81 GY 2201937 PHOENIX CONTACT DIN rail bus connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 TBUS 1,5/ 5-ST-3,81 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 TBUS 1,5/ 5-ST-3,81 GY
Catalog number	2201937
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-F2F29B6590
Generated	2026-08-06

Product Overview

DIN rail bus connectors

Bus connectors for rail, color: gray, rated current: 8 A (parallel contacts), rated voltage (III/2): 125 V, number of poles: 5, item family: TBUS5-22.5..., pitch: 3.81 mm, mounting: Rail mounting, lock: without, fixing type: without, packaging type: packed in box, Items with gold contacts, bus connectors for connection with electronics boxes, 5 contacts in parallel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2201937

Packing unit 1

GTIN 4046356939911

Custom tariff number 85366990

Standards and Regulations

Connection in acc. with standard CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 4.0EC001031ETIM 5.0EC002638ETIM 6.0EC001031

UNSPSC 13.231261501

ETIM for 2201937 Connectors (EC002637)

Feature Name

Feature Value

Modular spacing contacts (EF007326)

3.81 mm

Modular spacing connections (EF006827)

3.81 mm

Rated current In (EF008250)

8 A

Rated voltage (EF000228)

125 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Type of electric connection (EF003961)

Other

Suitable for PCB thickness (EF007253)

1.8 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Grey

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of fastening (EF002442)

Other

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 TBUS 1,5/ 5-ST-3,81 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.