

INDUSTRIAL COMPONENT DATA

ME 22,5 UT/FE BUS 2P+10 GY 2203506 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 UT/FE BUS 2P+10 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 UT/FE BUS 2P+10 GY
Catalog number	2203506
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-3BA168F068
Generated	2026-08-06

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, with vents, width: 22.6 mm, height: 99 mm, depth: 107.3 mm

Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, color: gray (7042), cross bridge: integrated bus connector, number of poles cross connector: 2+10, Bus connector: 2 parallel contacts, 10 series contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2203506

Packing unit 1

GTIN 4055626622460

Custom tariff number 85389099

Item properties

Material data

PCB data

Power dissipation, single housing at 30 °C

Power dissipation, single housing at 50 °C

Mechanical strength/tumbling barrel

Shock

Test for assessing the risk of fire (glow wire)

General information

Standards and regulations

Dimensions

Ambient conditions

Power dissipation, single housing at 20 °C

Power dissipation, single housing at 40 °C

Power dissipation, single housing at 60 °C

Vibration test

Thermostability (Ball Thrust Test)

Degrees of protection provided by housings (IP code)

Packaging information

Classifications

Item properties

Brief article description Mounting base housing

Type ME 22,5 UT/FE BUS 2P+10 GY

Order No. 2203506

Housing type DIN rail housing

Type Lower housing part with metal foot catch, tall design

Max. IP code to attain IP20

Mounting type DIN rail mounting

Ventilation openings present yes

[Back to top](#)Dimensions

Width [w] 22.6 mm

Height [h] 99 mm

Depth [d] 107.3 mm

Depth from top edge of DIN rail [d] 99.8 mm

Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm

[Back to top](#)Material data

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (stora...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 UT/FE BUS 2P+10 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.