

INDUSTRIAL COMPONENT DATA

ME 22,5 UTL H BUS 10/2 GY 1468250 PHOENIX CONTACT DIN rail housing, Housing half-frame (left), tall design, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 UTL H BUS 10/2 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 UTL H BUS 10/2 GY
Catalog number	1468250
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-8B1950FB41
Generated	2026-08-03

Product Overview

DIN rail housing, Housing half-frame (left), tall design, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, colour: grey (similar RAL 7042)

Rail box, Housing half-frame (left), tall design, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, colour: luminous grey (7035)

DIN rail housing, Housing half shell (left), tall design, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, color: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

Product propertiesProduct type Enclosure bottom part

Product family ME..UT

Type Housing half shell (left), tall design

Housing type DIN rail housing

Ventilation openings present yes

Housing series ME

DimensionsWidth 22.6 mm

Height 99 mm

Depth 107.3 mm

Depth from top edge of DIN rail 100.7 mm
Depth from top edge of DIN rail to support point on upper part 68.5 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specifications Color light grey (7035)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Surface characteristics untreated
Housing material Polyamide
Environmental and real-life conditions Vibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60998-1:2002-12
Height of fall 50 cm
Frequency 10
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Half-sine
Acceleration 15g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Degree of protection (IP code)
Specif...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 UTL H BUS 10/2 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.