


INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/ 5-G GY7035 1751590 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 5-G GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/ 5-G GY7035
Catalog number	1751590
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-5FA6BBB1B1
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: luminous gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: MSTBVA 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed
PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 5, pitch: 5 mm, color: light gray, contact surface: Tin, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Data commercial

Key order One million seven hundred fifty one thousand five hundred ninety

Packing unit 50 pcs

Key selling AAAFEA -

Minimum order quantity 50 pcs

EAN Four trillion forty six billion three hundred fifty six million three hundred seventeen thousand six hundred eighty nine

Unit weight (excluding packaging) 1,736 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin DE (Germany)

Drawings

Overview

Environmental Product Compliance

Dimensions

Standards and specifications

Ratings

Drawings

Diagram

Type: MSTB 2,5/...-ST with MSTBVA 2,5/...-G

Diagram

Type: SMSTB 2,5/...-ST with MSTBVA 2,5/...-G

Diagram

Type: FKCT 2,5/...-ST with MSTBVA 2,5/...-G

Diagram

Type: MSTBT 2,5/...-ST with MSTBVA 2,5/...-G

Diagram

Type: MSTBP 2,5/...-ST with MSTBVA 2,5/...-G

Diagram

Type: FKCN 2,5/...-ST with MSTBVA 2,5/...-G

Diagram

Type: FKCV(W/R) 2,5/...-ST with MSTBVA 2,5/...-G

Back to topDimensions

Length [l] 8.57 per mm

Width 27 mm

Step 5 mm

Average 20 mm

Width [w] 27 mm

Height [h] 15.9 mm

Height of construction 12 mm

Length of the pin welding 3.9 mm

Dimensions of pin 1 x 1 mm

Length 8.57 per mm

Back to topOverview

Family of articles MSTBVA 2,5/...-G -

Tension and sizing (III/3) 250 V

Connection according to standard EN-VDE

Nominal current IN 12 To

Color light grey

Number of poles Five

Back to topStandards and specifications

Connection according to standard EN-VDE

Back to topEnvironmental Product Compliance

China RoHS Space o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 5-G GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.