

INDUSTRIAL COMPONENT DATA

ME 35 UT/FE BUS/10+2 BK 2200400 PHOENIX CONTACT

Component housing, length: 99 mm, with vents, Lower part, Cr..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 35 UT/FE BUS/10+2 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 35 UT/FE BUS/10+2 BK
Catalog number	2200400
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-771D937AEA
Generated	2026-08-06

Product Overview

Component housing, length: 99 mm, with vents, Lower part, Cross connection: integrated bus connector, color: black, width: 35 mm, height: 114.5 mm, number of positions cross connector: 10+2

Rail box, Lower part of the housing with metal pin, with 2 FE contacts, high design, with ventilation slits, width: 35.2 mm, height: 99 mm, depth: 107.3 mm, color: black (9005), cross bridge: integrated bus connector, number of poles cross connector: 10+2, Bus connector: 10 parallel contacts, 2 series contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Component housing, length: 99 mm, with vents, Lower part, Cross connection: integrated bus connector, color: black, width: 35 mm, height: 114.5 mm, number of positions cross connector: 10+2

Key Commercial Data

Orderkey 2200400

Packing unit 1

GTIN 4046356570176

Custom tariff number 85369010

General

Housing type Component housing

Housing material Polyamide

Color (RAL) black

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C (depending on power dissipation)

Dimensions

Length 99 mm

Height 114.5 mm

Width 35 mm

Depth 99 mm

Technical data

Power dissipation without gap 7.9 W

Power dissipation with 20 mm gap 16.3 W

Number of positions 24

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0 27180401

eCl@ss 4.1 27180401

eCl@ss 5.0 27180505

eCl@ss 5.1 27180500

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

ETIM

ETIM 2.0 EC001031

ETIM 3.0 EC001031

ETIM 4.0 EC001031

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

UNSPSC

UNSPSC 6.01 31261501

UNSPSC 7.0901 31261501

UNSPSC 11 31261501

UNSPSC 12.01 31261501

UNSPSC 13.2 31261501

ETIM for 2200400 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 35 UT/FE BUS/10+2 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.