

INDUSTRIAL COMPONENT DATA

ME 52,5 UT/FE BUS/10 KMGY 2854067 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catch..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 52,5 UT/FE BUS/10 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 52,5 UT/FE BUS/10 KMGY
Catalog number	2854067
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-2D6D03063C
Generated	2026-08-06

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, with vents, width: 52.5 mm, cross connection: integrated bus connector, number of positions cross connector: 10, color: light gray (7035)

Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 52.5 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035), cross bridge: integrated bus connector, number of poles cross connector: 10, Bus connector: 10 contacts in parallel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2854067

Packing unit 1

GTIN 4017918459055

Custom tariff number 85369010

Item properties

Material data

PCB data

Packaging information

Environmental Product Compliance

Dimensions

Ambient conditions

General information

Standards and regulations

Classifications

Item properties

Brief article description Mounting base housing

Type ME 52,5 UT/FE BUS/10 KMGY

Order No. 2854067

Housing type DIN rail housing

Type Lower housing part with metal foot catch, tall design

Max. IP code to attain IP20

Mounting type DIN rail mounting

Ventilation openings present yes

[Back to top](#)Dimensions

Width [w] 52.5 mm

Depth from top edge of DIN rail [d] 99.8 mm

Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm

[Back to top](#)Material data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)PCB data

PCB thickness 1.4 mm ... 1.8 mm

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

[Back to top](#)General information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Type of note Recommendation

Note Material of contact pads for bus connector, galvanic gold (hard gold)

[Back...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 52,5 UT/FE BUS/10 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.