

INDUSTRIAL COMPONENT DATA

ME 67,5 UTG/FE KMGY 1005094 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catch, tall..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 67,5 UTG/FE KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 67,5 UTG/FE KMGY
Catalog number	1005094
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-D18C381C9D
Generated	2026-08-06

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, without vents, width: 67.8 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035)

Rail box, Bottom of the box with metal pin, with 3 FE contacts, high design, without ventilation slits, width: 67.8 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035), cross bridge: without bus connector, number of poles cross connector: not relevant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
 Orderkey 1005094
 Packing unit 1
 GTIN 4055626474960
 Custom tariff number 85472000
 Item properties
 Material data
 PCB data
 Packaging information
 Classifications
 Dimensions

Ambient conditions

General information

Standards and regulations

Item properties

Brief article description Mounting base housing

Type ME 67,5 UTG/FE KMGY

Order No. 1005094

Housing type DIN rail housing

Type Lower housing part with metal foot catch, tall design

Max. IP code to attain IP20

Mounting type DIN rail mounting

Ventilation openings present no

Back to topDimensions

Width [w] 67.8 mm

Height [h] 99 mm

Depth [d] 107.3 mm

Depth from top edge of DIN rail [d] 99.8 mm

Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm

Back to topMaterial data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polyamide

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

Back to topPCB data

Number of PCB holders 3

PCB thickness 1.4 mm ... 1.8 mm

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

Back to topGeneral information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Type of note Recommendation

Note Material of contact pads for bus connector, galvani...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 67,5 UTG/FE KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.