

INDUSTRIAL COMPONENT DATA

ME-IO 75,2 EB/FE4 10U TBUS 7035 1458284 PHOENIX CONTACT DIN rail housing, Housing bottom with metal pin, wit..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME-IO 75,2 EB/FE4 10U TBUS 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME-IO 75,2 EB/FE4 10U TBUS 7035
Catalog number	1458284
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-7933D88FE2
Generated	2026-08-06

Product Overview

DIN rail housing, Housing bottom with metal pin, with ventilation slits, width: 75.87 mm, height: 120.6 mm, depth: 82.85 mm, colour: light grey (similar to RAL 7035), cross bridge: DIN rail bus connector (optional), number of cross connector poles: 5 or 8

Rail box, Bottom of housing with metal pin, with ventilation slits, width: 75.87 mm, height: 120.6 mm, depth: 82.85 mm, colour: light grey (7035), cross-bridge: Bus connector for rail (optional), number of poles cross connector: 5 or 8

DIN rail housing, Lower housing part with metal foot catch, with vents, width: 75.87 mm, height: 120.6 mm, depth: 82.85 mm, color: light grey (7035), cross connection: DIN rail connector (optional), number of positions cross connector: 5 or 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

General Material of contact pads for bus connector, galvanic gold (hard gold)

Product propertiesProduct type Enclosure bottom part

Max. number of positions 192 (pitch: 3.45 mm)

128 (pitch: 5 mm)

Type Lower housing part with metal foot catch

Housing type DIN rail housing

Ventilation openings present yes
Housing series ME-IO
Connection data Cross section AWG (converted acc. to IEC)
Dimensions Dimensional drawing
Width 75.87 mm
Height 120.6 mm
Depth 82.85 mm
Depth from top edge of DIN rail 76.25 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specifications Color light grey (7035)
Flammability rating according to UL 94 V0
Surface characteristics untreated
Housing material Polyamide
Environmental and real-life conditions Power dissipation single housing for 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 33.7 W
Power dissipation single housing for 30 °C
Ambient temperature 30 °C
Reduction factor 0.82
Mounting position vertical
Power dissipation 27.6 W
Power dissipation single housing for 40 °C
Ambient temperature 40 °C
Reduction factor 0.62
Mounting position vertical
Power dissipation 21 W
Power dissipation single housing for 50 °C
Ambient temperature 50 °C
Reduction factor 0.46
Mounting position vertical
Power dissipation 15.5 W
Power dissipation single housing for 60 °C
Ambient temperature 60 °C
Reduction factor 0.3
Mounting position vertical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME-IO 75,2 EB/FE4 10U TBUS 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.