


INDUSTRIAL COMPONENT DATA

ME-IO 75,2 LB 10U TBUS 7035 2202620 PHOENIX CONTACT

Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME-IO 75,2 LB 10U TBUS 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME-IO 75,2 LB 10U TBUS 7035
Catalog number	2202620
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-0CA7CCB7F5
Generated	2026-08-05

Product Overview

Mounting base housing

Rail housing, Lower part of housing with metal pin, with ventilation slits, width: 75.87 mm, height: 120.6 mm, depth: 64.3 mm, colour: light grey (7035), cross bridge: Rail bus connector (optional), number of poles cross connector: 5 or 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2202620

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626199252

Weight per Piece (excluding packing) 69.100 g

Custom tariff number 85472000

Country of origin DE (Germany)

Item properties

Brief article description Mounting base housing

Type ME-IO 75,2 LB 10U TBUS 7035

Order No. 2202620

Housing type Component housing

Type Lower part

Max. IP code to attain IP20

Mounting type DIN rail mounting

Ventilation openings present yes

Max. number of positions 156 (pitch: 3.45 mm)

104 (pitch: 5 mm)

Dimensions

Width [w] 75.9 mm

Height [h] 120.6 mm

Depth [d] 64.3 mm

Depth from top edge of DIN rail [d] 57.7 mm

Material data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polyamide

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

PCB data

PCB thickness 1.4 mm ... 1.8 mm

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

Packaging information

Type of packaging packed in cardboard

Pieces per package 10

Denomination packing units Pcs.

Outer packaging type Carton

Standards and regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME-IO 75,2 LB 10U TBUS 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.