


INDUSTRIAL COMPONENT DATA

ME-IO 75,2 LB/FE 10U TBUS 7035 2202621 PHOENIX CONTACT Component housing, Lower part, with vents, width: 75...

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME-IO 75,2 LB/FE 10U TBUS 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME-IO 75,2 LB/FE 10U TBUS 7035
Catalog number	2202621
Category	Extruded profile modular housing
Minimum order	3 Pcs
Document ID	EO-527AAA2282
Generated	2026-08-04

Product Overview

Component housing, Lower part, with vents, width: 75.9 mm, color: light gray (7035)

Rail housing, Lower part of housing with metal pin, with ventilation slits, width: 75.87 mm, height: 120.6 mm, depth: 64.3 mm, colour: light grey (7035), cross bridge: Rail bus connector (optional), number of poles cross connector: 5 or 8

DIN rail housing, Lower housing part with metal foot catch, with vents, width: 75.87 mm, height: 120.6 mm, depth: 64.3 mm, color: light gray (similar RAL 7035), cross connection: DIN rail connector (optional), number of positions cross connector: 5 or 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Recommendation Material of contact pads for bus connector, galvanic gold (hard gold)

Product propertiesProduct type Enclosure bottom part

Housing type DIN rail housing

Housing series ME-IO

Max. number of positions 156 (pitch: 3.45 mm)

104 (pitch: 5 mm)

Type Lower housing part with metal foot catch

Ventilation openings present yes
Data management status
Article revision 04
DimensionsDimensional drawing
Width 75.87 mm
Height 120.6 mm
Depth 64.3 mm
Depth from top edge of DIN rail 57.7 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsPower dissipation single housing for 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 25 W
Power dissipation single housing for 30 °C
Ambient temperature 30 °C
Reduction factor 0.82
Mounting position vertical
Power dissipation 20.5 W
Power dissipation single housing for 40 °C
Ambient temperature 40 °C
Reduction factor 0.62
Mounting position vertical
Power dissipation 15.5 W
Power dissipation single housing for 50 °C
Ambient temperature 50 °C
Reduction factor 0.46
Mounting position vertical
Power dissipation 11.5 W
Power dissipation single housing for 60 °C
Ambient temperature 60 °C
Redu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME-IO 75,2 LB/FE 10U TBUS 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.