

**INDUSTRIAL COMPONENT DATA**

# ME MAX 12,5 PLATE KMGY 2201256 PHOENIX CONTACT

## Component housing, Complete housing, color: light gray

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 12,5 PLATE KMGY



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME MAX 12,5 PLATE KMGY           |
| Catalog number  | 2201256                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-BA9D9C9A36                    |
| Generated       | 2026-08-04                       |

### Product Overview

Component housing, Complete housing, color: light gray

Rail box, Insertable blind cover, width: 9.2 mm, height: 73.6 mm, depth: 1 mm, colour: light grey (7035)

DIN rail housing, Insertion plate, width: 9.2 mm, height: 73.6 mm, depth: 1 mm, color: light gray (similar RAL 7035)

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Cover

Housing type DIN rail housing

Housing series ME-MAX

Product family ME MAX 12,5..

Type Insertion plate

Ventilation openings present no

Data management status

Article revision 00

DimensionsWidth 9.2 mm

Height 73.6 mm

Depth 1 mm

Material specificationsColor (Insertion plate) light gray (RAL 7035)

Flammability rating according to UL 94 V0

CTI according to IEC 60112 600

Housing material Polyamide

Surface characteristics untreated

Environmental and real-life conditions Ambient conditions

Max. IP code to attain IP20

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Relative humidity (storage/transport) 80 %

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 12,5 PLATE KMGY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.