

**INDUSTRIAL COMPONENT DATA**

# ME MAX 17,5 2-2 BU 1129107 PHOENIX CONTACT DIN rail housing, Complete housing with metal foot catch, tall de..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 17,5 2-2 BU



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | PHOENIX CONTACT      |
| MPN / Reference | ME MAX 17,5 2-2 BU   |
| Catalog number  | 1129107              |
| Category        | Electronic enclosure |
| Minimum order   | 100 Pcs              |
| Document ID     | EO-D284DD43ED        |
| Generated       | 2026-08-06           |

## Product Overview

DIN rail housing, Complete housing with metal foot catch, tall design, with vents, width: 17.5 mm, height: 99 mm, depth: 114.5 mm, color: blue (5015)

Rail box, Full housing with metal pin, tall design, with ventilation slits, width: 17.6 mm, height: 99 mm, depth: 113.65 mm, color: blue (5015), cross bridge: Rail bus connector (optional), number of poles cross connector: 5

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Housing (HS)

## Additional Product Information

Key Commercial Data  
 Orderkey 1129107  
 Packing unit 1  
 GTIN 4063151056766  
 Custom tariff number 85389099  
 Drawings  
 Dimensions  
 Ambient conditions  
 General information  
 Standards and regulations  
 Item properties  
 Material data

[PCB data](#)

[Packaging information](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to topItem properties](#)

[Brief article description Electronic housing](#)

Type ME MAX 17,5 2-2 BU

Order No. 1129107

[Housing type DIN rail housing](#)

Type Complete housing with metal foot catch, tall design

Max. IP code to attain IP20

[Mounting type DIN rail mounting](#)

Number of levels 2

[Connection levels 2 \(Both sides\)](#)

[Ventilation openings present yes](#)

Max. number of positions 16 (pitch: 3.5 mm)

12 (pitch: 5 mm)

8 (pitch: 7.25 mm/7.5 mm)

[Back to topDimensions](#)

[Dimensional drawing](#)

Width [ w ] 17.5 mm

Height [ h ] 99 mm

Depth [ d ] 114.5 mm

Depth from top edge of DIN rail [ d ] 107 mm

[Back to topMaterial data](#)

Color (RAL) blue (5015)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to topAmbient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to topPCB data](#)

Number of PCB holders 1

[Mounting position Vertical \(horizontal DIN rail\)](#)

Type of PCB mount Latching

[Back to topGeneral information](#)

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download are...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 17,5 2-2 BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.