

INDUSTRIAL COMPONENT DATA

ME MAX 17,5 GEH-R CL G3-3 PGBU 2203941 PHOENIX CONTACT DIN rail housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 17,5 GEH-R CL G3-3 PGBU



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 17,5 GEH-R CL G3-3 PGBU
Catalog number	2203941
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-271D036B0F
Generated	2026-08-05

Product Overview

DIN rail housing

Rail housing, Housing half-frame (right), tall design, no ventilation slits, width: 11.3 mm, height: 99 mm, depth: 112.85 mm, colour: columbian blue (similar RAL 5014), transverse bridge: rail bus connector (optional)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2203941

Packing unit 1

GTIN 4055626460529

Custom tariff number 85389099

Item properties

Ambient conditions

General information

Standards and regulations

Material data

PCB data

Packaging information

Classifications

Item properties

Brief article description Housing half shell

Type ME MAX 17,5 GEH-R CL G3-3 PGBU

Order No. 2203941

Housing type DIN rail housing

Type

Max. IP code to attain IP20

Mounting type DIN rail mounting

[Back to top](#)Material data

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)PCB data

Mounting position Vertical (horizontal DIN rail)

Type of PCB mount Latching

[Back to top](#)General information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Type of note Recommendation

Note Material of contact pads for bus connector, galvanic gold (hard gold)

[Back to top](#)Packaging information

Pieces per package 50

Denomination packing units Pcs.

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Classifications

eCl@ss

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)ETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

[Back to top](#)

ETIM for 2203941 Low-voltage industrial...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 17,5 GEH-R CL G3-3 PGBU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.