

INDUSTRIAL COMPONENT DATA

ME MAX 22,5 GEH-R G 2-2 YE 2202150 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 22,5 GEH-R G 2-2 YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 22,5 GEH-R G 2-2 YE
Catalog number	2202150
Category	Extruded profile modular housing
Minimum order	50 Pcs
Document ID	EO-4B8DB0DF8C
Generated	2026-08-06

Product Overview

Electronic housing

Rail housing, Housing half-frame (right), width: 16.3 mm, height: 99 mm, depth: 112.85 mm, colour: yellow (1018)

DIN rail housing, Housing half shell (right), width: 16.3 mm, height: 99 mm, depth: 112.85 mm, color: yellow (similar RAL 1018)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Recommendation Material of contact pads for bus connector, galvanic gold (hard gold)

Product propertiesProduct type Housing half shells

Housing type DIN rail housing

Housing series ME-MAX

Product family ME MAX.. 2-2

Number of rows 2

Type Housing half shell (right)

DimensionsDimensional drawing

Width 16.3 mm

Height 99 mm

Depth 112.85 mm

Depth from top edge of DIN rail 107 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) yellow (RAL 1018)
Flammability rating according to UL 94 V0
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 %
PCB dataType of PCB mount Latching
Thickness of the PCB 1.4 mm ... 1.8 mm
MountingMounting type DIN rail mounting
ETIM for 2202150 Low-voltage industrial controls and switchgear (EC002779)
Feature Name
Feature Value
Type of enclosure (EF003086)
Open
Housing connectable (EF003088)
No
Suitable for rail mounting (EF003972)
No
Wall mounting possible (EF003973)
No
With integrated PCB-mounting connection system (EF003087)
No
Surface finishing (EF006569)
Other
Colour (EF000007)
Yellow
RAL-number (EF000116)
1018....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 22,5 GEH-R G 2-2 YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.