

**INDUSTRIAL COMPONENT DATA**

# ME MAX 45 MT 3-3 KMGY 2890975 PHOENIX CONTACT

## Components of electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 45 MT 3-3 KMGY



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME MAX 45 MT 3-3 KMGY            |
| Catalog number  | 2890975                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-D9F4BE3B5B                    |
| Generated       | 2026-08-04                       |

### Product Overview

Components of electronic housing

Rail box, Middle element, tall design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 112.85 mm, colour: light grey (7035)

DIN rail housing, Intermediate element, tall design, with vents, width: 22.6 mm, height: 99 mm, depth: 112.85 mm, color: light gray (similar RAL 7035)

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Complete housing center part

Housing type DIN rail housing

Housing series ME-MAX

Product family ME MAX.. 3-3

Number of rows 3

Type Intermediate element, tall design

Ventilation openings present yes

Data management status

Article revision 01

DimensionsDimensional drawing

Width 22.6 mm  
Height 99 mm  
Depth 112.85 mm  
Depth from top edge of DIN rail 107 mm  
Material specificationsColor (Housing) light gray (RAL 7035)  
Flammability rating according to UL 94 V0  
CTI according to IEC 60112 600  
Housing material Polyamide  
Surface characteristics untreated  
Environmental and real-life conditionsAmbient conditions  
Max. IP code to attain IP20  
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)  
Ambient temperature (storage/transport) -40 °C ... 55 °C  
Ambient temperature (assembly) -5 °C ... 100 °C  
Relative humidity (storage/transport) 80 %  
PCB dataType of PCB mount Latching  
MountingMounting type DIN rail mounting  
ETIM for 2890975 Low-voltage industrial controls and switchgear (EC002779)  
Feature Name  
Feature Value  
Type of enclosure (EF003086)  
Open  
Housing connectable (EF003088)  
No  
Suitable for rail mounting (EF003972)  
No  
Wall mounting possible (EF003973)  
No  
With integrated PCB-mounting connection system (EF003087)  
No  
Material (EF002169)  
Other  
Surface finishing (EF006569)  
Other  
RAL-number (EF000116)  
7035  
Width (EF000008)  
22.6 mm  
Height (EF0000...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 45 MT 3-3 KMGY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.