


INDUSTRIAL COMPONENT DATA

ME MAX 45 MT U-U1 KMGY 2200027 PHOENIX CONTACT DIN rail box, Intermediate element, high design, with ventila..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 45 MT U-U1 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 45 MT U-U1 KMGY
Catalog number	2200027
Category	Extruded profile modular housing
Minimum order	50 Pcs
Document ID	EO-F51401FBDA
Generated	2026-08-03

Product Overview

DIN rail box, Intermediate element, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 112.85 mm, color: light gray (similar RAL 7035)

Rail box, Middle element, tall design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 112.85 mm, colour: light grey (7035)

DIN rail housing, intermediate element, high design, with air vents, width: 22.6 mm, height: 99 mm, depth: 112.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataRemarksGeneral Please refer to the family data sheet in the download area.

Item propertiesProduct Type Complete housing middle section

Product family ME MAX.. U-U1

Number of rows 1

Execution Intermediate element, high design

Housing type DIN rail housing

Ventilation opening available Yes

Housing series ME-MAX

DimensionsWidth 22.6 mm

Height 99 mm

Depth 112.85 mm
Depth from top edge of the DIN rail 107 mm
Material specificationsColor Light Grey (7035)
Color (Housing) light grey (RAL 7035)
Flammability class according to UL 94 V0
CTI according to IEC 60112 600
Surface finish untreated
Material housing Polyamide
Environmental and lifetime conditionsEnvironmental conditions
Maximum IP code that can be reached IP20
Ambient temperature (operating) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (mounting) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 %
PCB InformationType of PCB mounting Latching
AssemblyMounting type DIN rail mounting
ETIM for 2200027 Low-voltage industrial controls and switchgear (EC002779)
Feature Name
Feature Value
Type of enclosure (EF003086)
Open
Housing connectable (EF003088)
No
Suitable for rail mounting (EF003972)
No
Wall mounting possible (EF003973)
No
With integrated PCB-mounting connection system (EF003087)
No
Material (EF002169)
Other
Surface finishing (EF006569)
Other
RAL-number (EF000116)
7035
Width (EF000008)
22.6 mm
Height (EF000040)
99 mm
Dept...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 45 MT U-U1 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.