

## INDUSTRIAL COMPONENT DATA

# ME MAX 90 DKL TRANS 1538952 PHOENIX CONTACT Rail box, Lid, width: 90.4 mm, height: 75.25 mm, depth: 5.5 mm, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 90 DKL TRANS



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME MAX 90 DKL TRANS              |
| Catalog number  | 1538952                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 100 Pcs                          |
| Document ID     | EO-0F5C1EB486                    |
| Generated       | 2026-08-04                       |

## Product Overview

Rail box, Lid, width: 90.4 mm, height: 75.25 mm, depth: 5.5 mm, colour: transparent

Rail Box, Full Housing with Metal Pin, Tall Design

DIN rail housing, Cover, width: 90.4 mm, height: 75.25 mm, depth: 5.5 mm, color: transparent

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

Product propertiesProduct type Cover

Product family ME MAX..DKL

Type Cover

Housing type DIN rail housing

Ventilation openings present no

Housing series ME-MAX

DimensionsWidth 90.4 mm

Height 75.25 mm

Depth 5.5 mm

Material specificationsColor transparent

Color (Housing) transparent

Flammability rating according to UL 94 V2

CTI according to IEC 60112 250  
Insulating material IIIa  
Surface characteristics untreated  
Housing material Polycarbonate  
Environmental and real-life conditions Ambient conditions  
Max. IP code to attain IP20  
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)  
Ambient temperature (storage/transport) -40 °C ... 70 °C  
Ambient temperature (assembly) -5 °C ... 100 °C  
Relative humidity (storage/transport) 95 %  
PCB data Type of PCB mount Latching  
ETIM for 1538952 Low-voltage industrial controls and switchgear (EC002779)  
Feature Name  
Feature Value  
Type of enclosure (EF003086)  
Closed  
Housing connectable (EF003088)  
No  
Suitable for rail mounting (EF003972)  
No  
Wall mounting possible (EF003973)  
No  
With integrated PCB-mounting connection system (EF003087)  
No  
Material (EF002169)  
Other  
Surface finishing (EF006569)  
Other  
Colour (EF000007)  
Other  
Width (EF000008)  
90.4 mm  
Height (EF000040)  
75.25 mm  
Depth (EF000049)  
5.5 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 90 DKL TRANS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.