

## INDUSTRIAL COMPONENT DATA

## ME MAX B-22,5 GN 2707916 PHOENIX CONTACT Filler plugs

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX B-22,5 GN



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME MAX B-22,5 GN                 |
| Catalog number  | 2707916                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-CBCC1FBCDE                    |
| Generated       | 2026-08-04                       |

## Product Overview

Filler plugs

Rail box, Blank plug for non-equipped terminal points, width: 20 mm, height: 21.6 mm, depth: 8.1 mm, colour: green (6021)

DIN rail housing, Filler plug for unoccupied terminal points, width: 20 mm, height: 21.6 mm, depth: 8.1 mm, color: green (similar RAL 6021)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Filler plug

Housing type DIN rail housing

Housing series ME-MAX

Product family ME MAX 22,5..

Type Filler plug for unoccupied terminal points

Ventilation openings present no

Data management status

Article revision 03

DimensionsWidth 20 mm

Height 21.6 mm

Depth 8.1 mm

Material specificationsColor (Housing) green (RAL 6021)

Flammability rating according to UL 94 V0  
CTI according to IEC 60112 600  
Housing material Polyamide  
Surface characteristics untreated  
Environmental and real-life conditions Ambient conditions  
Max. IP code to attain IP20  
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)  
Ambient temperature (storage/transport) -40 °C ... 55 °C  
Ambient temperature (assembly) -5 °C ... 100 °C  
Relative humidity (storage/transport) 80 %  
Mounting Mounting type Latching  
Packaging specifications Outer packaging type Resealable bag  
ETIM for 2707916 Low-voltage industrial controls and switchgear (EC002779)  
Feature Name  
Feature Value  
Type of enclosure (EF003086)  
Open  
Housing connectable (EF003088)  
No  
Suitable for rail mounting (EF003972)  
No  
Wall mounting possible (EF003973)  
No  
With integrated PCB-mounting connection system (EF003087)  
No  
Material (EF002169)  
Other  
Surface finishing (EF006569)  
Other  
Colour (EF000007)  
Green  
RAL-number (EF000116)  
6021

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX B-22,5 GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.