

INDUSTRIAL COMPONENT DATA

ME MAX B-22,5 RD S75 1030270 PHOENIX CONTACT DIN rail housing, Filler plug for unoccupied terminal points, w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX B-22,5 RD S75



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX B-22,5 RD S75
Catalog number	1030270
Category	Electronic enclosure
Minimum order	100 Pcs
Document ID	EO-1D1F82B246
Generated	2026-08-04

Product Overview

DIN rail housing, Filler plug for unoccupied terminal points, width: 20 mm, height: 21.6 mm, color: red (3001)

Rail box, Blank plug with ventilation slots for non-equipped terminal points, width: 20 mm, height: 21.6 mm, depth: 8.1 mm, colour: red (3001)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 1030270

Packing unit 1

GTIN 4055626533582

Custom tariff number 39269097

Item properties

Material data

General information

Standards and regulations

Dimensions

Ambient conditions

Packaging information

Classifications

Item properties

Brief article description Filler plugs

Type ME MAX B-22,5 RD S75

Order No. 1030270

Housing type DIN rail housing

Type Filler plug for unoccupied terminal points

Mounting type Latching

Back to topDimensions

Width [w] 20 mm

Height [h] 21.6 mm

Back to topMaterial data

Color (RAL) red (3001)

Flammability rating according to UL 94 V0

Housing material Polyamide

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

Back to topGeneral information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Back to topPackaging information

Pieces per package 50

Denomination packing units Pcs.

Outer packaging type Resealable bag

Back to topStandards and regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCl@ss

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

Back to topETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

Back to top

ETIM for 1030270 Low-voltage industrial controls and switchgear (EC002779)

Feature Nam...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX B-22,5 RD S75 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.