


INDUSTRIAL COMPONENT DATA

MFKDSP/ 7-5,08 BD:91-79 SO 1717576 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MFKDSP/ 7-5,08 BD:91-79 SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	MFKDSP/ 7-5,08 BD:91-79 SO
Catalog number	1717576
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-E3E8D181DA
Generated	2026-08-05

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 12 A, dimensioning voltage (III/2): 320 V, nominal cross-section: 1 mm², Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, article family: MFKDSP, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.3 mm, packaging type: boxed

PCB terminal, rated current: 12 A, rated voltage (III/2): 320 V, rated cross-section: 1 mm², number of potentials: 7, number of rows: 1, number of poles per row: 7, item family: MFKDSP, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 45°, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.3 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1717576

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356139625

Weight per Piece (excluding packing) 7.360 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 16.2 mm

Pitch 5.08 mm

Dimension a 30.48 mm

Width [w] 35.56 mm

Height 12.92 mm

Height [h] 16.22 mm

Solder pin [P] 3.3 mm

Pin spacing 10.16 mm

Hole diameter 1.3 mm

General

Range of articles MFKDSP

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 1 mm²

Solder pin surface

Stripping length 10 mm

Number of positions 7

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC
13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MFKDSP/ 7-5,08 BD:91-79 SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.