

INDUSTRIAL COMPONENT DATA

MKDSO 2,5/ 3-R GY ANGEZ.SCHR. 2735506 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSO 2,5/ 3-R GY ANGEZ.SCHR.



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSO 2,5/ 3-R GY ANGEZ.SCHR.
Catalog number	2735506
Category	Printed circuit board terminal
Minimum order	200 Pcs
Document ID	EO-0B8677DF56
Generated	2026-08-05

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of rows: 1, number of poles per row: 3, family of articles: MKDSO 2.5/.. -R, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed packaging. Item with right-hand side pin output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 2735506

Packing unit 50 pc

GTIN 4017918585907

Weight per Piece (excluding packing) 5.520 g

Custom tariff number 85369010

Country of origin DE (Germany)

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC
13.239121432

ETIM for 2735506 Connectors (EC002643)

Feature Name**Feature Value**

Height (EF000040)

18.05 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current In (EF008250)

24 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section multi-wired (EF007343)

0.14 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF00682...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSO 2,5/ 3-R GY ANGEZ.SCHR. with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.