

INDUSTRIAL COMPONENT DATA

MINI MCR-2-UNI-UI-2UI-PT 2905028 PHOENIX CONTACT

Signal duplicator

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-2-UNI-UI-2UI-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI MCR-2-UNI-UI-2UI-PT
Catalog number	2905028
Category	Isolation amplifier
Minimum order	1 Pcs
Document ID	EO-4F1352A1EF
Generated	2026-08-04

Product Overview

Signal duplicator

Configurable 4-way universal signal duplicator with plug-in connection technology for duplication and galvanic separation of analogue signals. Configurable via DIP switches or software. Push-in connection technology, standard configuration.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2905028

Packing unit 1 pc

Catalog page Page 76 (C-5-2017)

GTIN 4046356915250

Weight per Piece (excluding packing) 62.900 g

Custom tariff number 85437090

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 110.5 mm

Depth 120.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Input data

Number of inputs 1

Configurable/programmable Yes

Voltage input signal 0 V ... 10 V (via DIP switch)

2 V ... 10 V (via DIP switch)

0 V ... 5 V (via DIP switch)

1 V ... 5 V (via DIP switch)

0 V ... 12 V (can be set via software)

Current input signal 0 mA ... 20 mA (via DIP switch)

4 mA ... 20 mA (via DIP switch)

0 mA ... 10 mA (via DIP switch)

20 mA ... 0 mA (via DIP switch)

0 mA ... 24 mA (can be set via software)

max. input voltage 12 V

Max. input current 24 mA

Input resistance of voltage input > 120 k?

Input resistance current input approx. 50 ? (+ 0.7 V for test diode)

Output data

Number of outputs 2

Voltage output signal 0 V ... 10 V (via DIP switch)

2 V ... 10 V (via DIP switch)

0 V ... 5 V (via DIP switch)

1 V ... 5 V (via DIP switch)

0 V ... 10.5 V (can be set via software)

Current output signal 0 mA ... 20 mA (via DIP switch)

4 mA ... 20 mA (via DIP switch)

0 mA ... 10 mA (via DIP switch)

20 mA ... 0 mA (via DIP switch)

0 mA ... 21 mA (can be set via software)

Max. output...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-2-UNI-UI-2UI-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.